



Technical Data Oil Spot Primer

REV 7/24

DESCRIPTION:

A polymer modified emulsion designed to seal oil and gasoline stains prior to applying GemSeal Driveway Sealers or Resurfacers. Dries clear.

FEATURES:

- Seals & Primes Oil & Grease Spots on Asphalt Driveways
- Improves Adhesion of Driveway Sealer
- Reduces Oil Spot Bleed-Through

USES:

Priming Oil & Gas Stains on Asphalt Pavement Prior to Applying Driveway Sealer

SURFACE PREPARATION:

For best results, scrub oil and grease stains with stiff brush or broom, household detergent, and water. Rinse thoroughly with water.

APPLICATION:

Mix contents of container by moderate shaking. Apply oil spot primer to stained areas. Spread with paint brush or other suitable brush. A second coat of oil spot primer may be applied for added bleed-through resistance. Oil Spot Primer must be completely dry before applying driveway sealer.

DRYING TIME:

Typically, drying time is 1-2 hours.

CLEAN UP:

- While wet, use soap and water.
- When dry, use paint thinner.

WEATHER CONDITIONS:

Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period.

COVERAGE (APPROXIMATE):

One .9 quart will cover approximately 30-50 square feet (one coat).

PRECAUTIONS:

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze

- Do Not Allow Traffic Until Fully Cured

SAFETY & ENVIRONMENTAL PRECAUTIONS:

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

Ingredients	Cas No.
Polymer Latex	Proprietary
Water	7732-18-5

MANUFACTURING & CUSTOMER SERVICE:

Visit gemsealproducts.com or phone 866-264-8273 to find the location near you.

LIMITED WARRANTY

The statements made on this technical data sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose.