



Technical Data

Rapid Set Additive

REV 7/24

DESCRIPTION:

GemSeal Rapid Set is a polymer emulsion admixture for use in asphalt emulsion and coal tar emulsion pavement sealers to reduce drying time and enhance coating performance.

FEATURES:

- Greatly reduces curing time of applied sealer dependent on percentage used
- Reduces the amount of power steering marks in the finished surface
- Compatible with coal tar and asphalt emulsion
- Improves adhesion and durability
- Enhances and darkens color of finished products
- Greater tensile strength and durability

USES:

Reduces the curing time and reduces occurrence and severity of power steering marks in the cured sealer coating. Improves adhesion and durability of pavement coating.

COMPOSITION:

GemSeal Rapid Set admixture is a unique copolymer emulsion especially designed for use with asphalt and coal tar based pavement sealers.

FORMULATIONS:

Numerous design mixes are available to meet varied job-site paving conditions. Typical design recommends addition of 2 to 5 gallons per 100 gallons of GemSeal Pavement Sealer Concentrate.

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

CLEANUP:

Spillage may be easily removed with water if still wet.

SERVICE:

Timely service is available within a 300 mile radius of our manufacturing facilities.

ATTENTION:

GemSeal Rapid Set should be protected from freezing.

CAUTION:

May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.

WARNING:

This product may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Twenty-five percent of the mixture consists of ingredient(s) of unknown acute toxicity.

MANUFACTURING & CUSTOMER SERVICE:

Visit gemsealproducts.com or phone 866-264-8273 to find the location near you.

LIMITED WARRANTY

The statements made on this technical data sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose.